

FEATURES

- Rugged piston construction built to withstand pressure ratings to 1500 psi
- Angle body design for high flows
- Ideal for high-pressure water applications, such as car washes
- Mountable in any position

STANDARD VOLTAGES

DC (=) : 24V

AC (~) : 110V - 120V - 220V - 230V - 240V / 50 - 60 Hz



SPECIFICATIONS

Pipe Size (in)	Orifice Size (mm)	Kv Flow Factor (m³/h)	Operating Pressure Differential (bar)							Max. Fluid Temp. °C		Prefix					Catalog Number	
			Min.	Max. AC			Max. DC											
				Air-Inert Gas	Water	Light Oil @ 300 SSU	Air-Inert Gas	Water	Light Oil @ 300 SSU	AC	DC	VC	EF/VCEF ⁽¹⁾	HB	Red Hat II NEMA 4	Brass	Stainless Steel	
NC - Normally closed (Closed when de-energized)																		
3/8	8	1.3	0.7	52	52	52	28	28	28	93	65	-	●	-	●	8223G023	-	
1/2	10	2.7	1.7	103	103	103	34	34	34	93	65	●	●	●	●	8223G003	-	
1/2	10	2.7	1.7	103	103	103	34	34	34	93	65	●	●	●	●	-	8223G010	

• Available Express

(1) VCEF can be mounted in 4 directions & 3 conduit sizes