


SOLENOID VALVES

direct operated
brass or stainless steel bodies
1/8 - 3/8

NO



2/2
Series
262

FEATURES

- Reliable, proven design with high flows
- Small poppet valves for tight shutoff
- Wide range of elastomers for specialty service
- Mountable in any position
- Brass and stainless steel constructions

STANDARD VOLTAGES

DC (=) : 24V

AC (~) : 110V - 120V - 220V - 240V / 50 - 60 Hz



SPECIFICATIONS

Pipe Size (in)	Orifice Size (mm)	Kv Flow Factor (m³/h)	Min Press	Operating Pressure Differential (bar)						Max. Fluid Temp °C		Prefix		Catalog Number
				Max AC @ 55°C			Max DC @ 55°C							
				Air-Inert Gas	Water	Lt. Oil @300 SSU	Air-Inert Gas	Water	Lt. Oil @300 SSU	AC	DC	EF/VCEF ⁽¹⁾	Red Hat II NEMA 4	
1/4	1.2	0.05	0	52	52	52	45	39	28	82	82	●	●	8262H260
1/4	2.4	0.18	0	19	16	12	11	9	7	82	82	●	●	8262H261

• Available Express

(1) VCEF can be mounted in 4 directions & 3 conduit sizes